

Accessories - Micro switches			
Switch Position Indicator		EV-LT00, EV-LTL123-1	EV-LTL123-3, EV-LTL4A
Fuse Blown Position Indicator		K-LTL** -1/H	K-LTL** -3/H, K-LTL4A
Rated Current @ 250V AC	A	5	8
Rated Current @ 110V DC	A	0.35	0.6
Electrical Life @ AC11	[No. of Operations]	100,000	50,000

D - Type Fuse Bases	
- Rated Current: 25A and 63A	
- Rated Voltage: 25A - 500V, 63A - 690V	
- Standard: IEC269-3-1	
- Flame Resistance to: UL94V-ø	
- Terminal: Clamp Type, self lifting, 25mm ² max.	
- Touch Protection: Clip-on Covers for top, bottom and sides are available.	
- Mounting: On Busbars 12-30mm width, 5 or 10mm thick.	

Terminal with Connecting Lug						
	AL/Cu Cable [mm ²]				Allen Key	Tightening Torque (Nm)
	Rounded Stranded	Sector Stranded	Round Solid	Sector Solid		
K2G/A	35-185	35-185	35-185	50-185	6 mm	40
KM2G/AF3040	25-300	25-240	25-150	25-240	6 mm	40
K2HG/2/AF30	2 x	2 x	2 x	2 x	6 mm	40
	25-120	35-120	25-50	50-120		
KV2HG/2/AF30	2 x	2 x	-	-	6 mm	40
	12 -185	12-185				

Fuse Switches Din Rail Mount		
	WH-AMB1/10 WH-AMB3/10	WH-AMB1/22 WH-AMB3/22
Rated Current @ 690V AC @ 440V DC	32A 32A	125A 125A
Application Category	AC-22B (400V)	AC-20B (690V)
Conditional Rated Short Circuit Current	50kA (400V)	100kA (500V)
Terminal Capacity	1x 0.75 - 25mm ² 2x 0.75 - 10mm ²	1x 4 - 50mm ²