



HRC Fuses

Type	SM000	SM00	SM1	SM2		SM3			SM4a	
500V A	4-100	125-160	6-250	50-250	315-400	50-400	425-500	630	50-1000	1250-1600
a <sub>1</sub>	78,5	78,5	135	150	150	150	150	150	200	200
a <sub>2</sub>	53	53	72	72	72	72	72	72	87	87
a <sub>4</sub>	50	50	67	67	67	67	67	67	90	90
b	15	15	20	20	26	26	32	37	50	50
c <sub>1</sub>	35	35	40	48	48	60	60	60	85	85
e <sub>1</sub>	40	47	50	50	59	59	69	69	95	106
e <sub>2</sub>	21	29	46	46	54	54	64	64	87	95
<b>Striker Fuses Only</b>										
T	17	17	26	26	26	26	26	26	26	26
R	0	0	13,7	16,2	16,2	17	17	17	24	24
P	20,5	20,5	20,5	27,3	27,3	35,6	35,6	35,6	49	49

Dimensions in mm

Semi Conductor Fuses

Type S	SM000	SM1	SM2	SM3
560/690V A	10-160	6-250	50-400	50-630
a <sub>1</sub>	78	135	150	150
a <sub>2</sub>	55	72	72	72
a <sub>4</sub>	48	65	65	65
b	15	24	30	37
c <sub>1</sub>	35	40	48	60
e <sub>1</sub>	49	52	61	74
e <sub>2</sub>	27	46	54	64

Dimensions in mm

aM Fuses

Type S	SM000	SM00	SM1	SM2	SM3
560V A	16-63	80-160	125-250	200-400	500-630
a <sub>1</sub>	78,5	78,5	135	150	150
a <sub>2</sub>	53	53	72	72	72
a <sub>4</sub>	50	50	67	67	67
b	15	15	20	26	37
c <sub>1</sub>	35	35	40	48	60
e <sub>1</sub>	40	47	49	58	73
e <sub>2</sub>	21	29	46	54	73

Dimensions in mm